



CEMENT & CONCRETE PRODUCTS™

STUCCO REPAIR

PRODUCT NO. 8650

PRODUCT DESCRIPTION

QUIKRETE® Stucco Repair is a superior crack filler and sealer for repairs to vertical and horizontal stucco surfaces.

PRODUCT USE

QUIKRETE® Stucco Repair fills and seals cracks in stucco up to 1/2" (12mm) wide. Weather resistant formula provides excellent adhesion and flexibility. The sanded acrylic formula is designed to blend in with the texture of stucco surfaces. Stucco Repair provides excellent adhesion and remains relatively flexible for durable repairs.

SIZES

• QUIKRETE® Stucco Repair is available in 5.5 oz (163 ml) squeeze tubes and 10.1 oz (296 ml) caulk tubes.

YIELD

• Each 10.1 oz (296 ml) tube will yield 24 linear feet (7.3 M) at 1/4" (6 mm) bead.

INSTALLATION

APPLICATION

Clean all dirt, dust, grease, and loose particles from the crack before filling. Cut the tip of the tube at an angle to make a 1/4" - 3/8" (6-9 mm) opening. Apply by pushing tube tip over the surface and squeezing a bead of Stucco Repair deep into the crack. Apply no thicker than 3/8" (9 mm) in one application. Stucco Repair can be tooled to match the existing surface texture. Excess material may be wiped off with a damp cloth.

DIVISION 9

Decorative Finishing
09 94 00



PRECAUTIONS

For best results, wait at least 24 hours before painting. Use latex paints only. Do not use to fill control / expansion joints. Do not use for structural repairs. Air and surface temperature should be above 40°F (4°C) for proper application. Do not apply if rain threatens or is predicted within 12 hours. Store between 35°F and 100°F (2°C and 38°C). Protect from freezing. Do not apply where temperatures may reach 140°F or higher (fireplaces, electric wires, etc.)

WARRANTY

NOTICE: Obtain the applicable LIMITED WARRANTY: at www.quikrete.com/product-warranty or send a written request to The Quikrete Companies, LLC, Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of The Quikrete Companies, LLC. © 2018 Quikrete International, Inc.